

Star-cleaner



CMN Star-cleaner – The optimal solution for breaking up the earth's crust and for mechanical weed control. The CMN Star-cleaner with three-point suspension is available in 3, 6, 8, 9, 10 and 12m working widths.

5 good reasons to choose the CMN Star-cleaner:

- 1. Gentle on crops, damage less than 4 -5%
- 2. Loosens the soil so that oxygen can reach the roots
- 3. Buggi-suspended stars ensure an even draft
- 4. The pressure can be set individually on each section
- 5. High capacity, driving speed 15-25 km / h





CMN Star-cleaner can be equipped with support wheels so that you can work at the desired depth or individually regulate the pressure on the stars, depending on what the machine is to work with.

The buggy- suspended Star rollers ensure that the machine runs evenly and at the same time compensates for unevenness.

The pressure on the individual buggy suspensions can be regulated by simply adjusting the springs in 4 different positions. The pressure can be of great importance, particularly in potatoes or specialty crops.





The distance between the individual star rolls is 12.5 cm. Together with the relatively large distance between the spade claws, the crop is only minimally damaged. When using the machine for weed control it is very important to start early as the greatest effect will be obtained by covering the weed.

<u>In other words - let the CMN Star-cleaner do jobs like breaking up the earth's crust and mechanical weed control</u>

Common technical specifications:

All machines are with three-point suspension. Power requirement 15 -20 HP/meter

Technical specifications Star-Cleaner

Туре	Working width cm	Transport width cm	Weight / kg	Number of stars	Sections
SR 300 (fix frame)	300	300	550	26	1
SR 400 (fix frame)	400	400	750	34	1
SR600	600	300	1150	50	1.5x3x1.5
SR800	800	300	1700	66	1x1.5x3x1.5x1
SR900	900	300	1950	74	1 x2x3x2x1
SR1000	1000	300	2220	82	1,5x2x3x2x1,5
SR1200	1200	325	2600	98	1,8x2,5x3,2x2.5x1,8

	maskintec vs
AC Hoppesvej 5	Tlf. +45 9787 2000
DK-7790 Thyholm	Fax +45 9787 2002
www.cmn.dk	mail@cmn.dk

Dealer:				